

D I G I T A L

Alcohol Detector

AlcoHAWK® Elite

Quick Results

**Easy
To Use**

**FDA 510(k)
Pre-Marketing Notification**

**Meets DOT/NHTSA
Standards for Screeners**

**4 Digit Blue
LCD Display**

Portable

**Multi-User
Mouthpiece Design**

**Breath Capture Sensor
Improves Sample Accuracy**

**Thermo-Check Sensor
Warns of Non-Optimal Temperature
Before Testing**



Patent #D521885








- The AlcoHAWK® Elite is a digital breath alcohol screener offering a brilliant blue LCD display and ergonomic grip.
- The AlcoHAWK® Elite incorporates professional features, such as pressure & temperature monitors, for high quality breath samples to enhance accuracy.
- The AlcoHAWK® Elite's professional features and design make it the favorite for the user who wants a unit with enhanced features.

AlcoHAWK® Elite

AlcoHAWK® Elite

The AlcoHAWK® Elite is a breath alcohol screener that quickly screens for the presence of alcohol. The AlcoHAWK® Elite includes a thermo sensor to ensure testing in optimal temperature range. Simply blow into the unit and within seconds the LCD displays a digital readout. The AlcoHAWK® Elite includes Sensor Recognition Technology™ to monitor certain types of abnormal sensor conditions. Passed FDA 510(k) pre-marketing notification and meets DOT/NHTSA model specifications for breath alcohol screeners.

Features

-  **Simple and easy to use**
-  **Four-digit LCD display**
-  **Beeps when ready to use**
-  **Beeps after breath sample obtained**
-  **Semi-conductor oxide sensor**
-  **Thermo sensor to ensure testing in optimal temperature range (50- 104 F)**
-  **Electric pressure sensor to improve breath capture quality**

Specifications

Dimensions	4 x 2.5 x 1 inches	Digital Display	4 Digits (0.000% B.A.C.)
Weight	.5 lbs	Operating Temp	10 - 40 c (50 - 104 f)
Housing	Shock Resistant, Molded Plastic	Detection Range	0.000% - 0.400% B.A.C.
Power	9 Volt Alkaline battery	Air Sample	5 Seconds
Battery Life	150 Tests ¹	Calibration	Required Periodically ³
Sensor	Sensitive Semi-conductor Sensor	Operation	1 Button
Blowing Time	5 Seconds	Limited Warranty	1 Year
Response Time	5 Seconds ¹	Accuracy	+/- 0.01% at 0.02% B.A.C. ²

¹ Estimates, results may vary.

² Read owner's manual before use and follow instructions carefully.

³ Visit www.q3i.com

© 2010 Q3 Innovations. All Rights Reserved.



Q3 Innovations www.q3i.com
 2349 Jamestown Avenue, Suite #4, Independence, Iowa 50644
 Tel: 319-334-3412 Fax: 319-334-3421 Email: sales@q3i.com