



Be sure to read the entire owner's manual and follow procedures carefully to obtain optimal results.

Operating Instructions

Wait 20 minutes after the subject smokes, eats or drinks before testing. Failure to wait 20 minutes can give inaccurate BAC readings and harm the sensor.

- Step 1) Place a fitted cover over the mouthpiece each time you test another individual.
- Step 2) If it has been more than 24 hours since the device was last used, prime the sensor by blowing into the mouthpiece for 4 to 5 seconds before turning on the device.
- Step 3) PRESS the red Power On/Off button and HOLD for one (1) second. A single beep will sound and the device will display the room temperature and then count down from 60 as it prepares the sensor for testing.

Note: The device will restart a count down from 10 if the sensor is not ready within the first countdown from 60.

Step 4) WAIT until the unit displays "Rdy", "BLOW" and you hear a SINGLE BEEP.

Note: The device will shut off after 15 seconds of non use.

Step 5) Take a DEEP BREATH AND BLOW STEADILY (for at least 5 seconds) until a BEEP sounds to signal completion of the testing.

THIS DEVICE IS INTENDED TO MEASURE ALCOHOL IN THE HUMAN BREATH.

DO NOT DRINK AND DRIVE.

SEE OWNER'S MANUAL FOR RE-CALIBRATION INSTRUCTIONS THAT MUST BE ROUTINELY PERFORMED.

Calibration Log Date First Used **Recalibration Date** Notes