DIGITAL
Alcohol Detector

AlcoHAWK®
PT500P

Quick Results

PT Core™
Electro-chemical Fuel-cell Sensor

**Easy-to-Read**
Orange LCD Display

Adjustable Blowing Time

Wireless Printing Capabilities*

Temperature Display

Switch Between
%BAC, g/L, or ‰BAC

Warning Level Indicator

*Wireless printer sold separately or with PT500P Professional Kit

🦅 A professional digital breath alcohol screener with wireless printing capabilities.

🦅 Features the new *PT Core*™ electro-chemical fuel-cell sensor and an advanced pressure scan sensor for reliable and accurate results.

🦅 Advanced features and design make it a favorite for law enforcement, clinics, corrections, schools, and other settings where professional alcohol testing is performed.

PT Core™ Technology

ADVANCED PRESSURECHECK TECHNOLOGY™

wireless ⇄ printing

AlcoHAWK® PT500P

DIGITAL
Alcohol Detector

AlcoHAWK®
PT500P

The AlcoHAWK® PT500P is a professional breath alcohol tester with wireless printing capabilities that is easy to use. Featuring the new *PT Core™* electro-chemical fuel-cell sensor, which is not subject to interference from acetone and offers greater linear accuracy and sensitivity than traditional semi-conductor testers. Its simple menu-driven operation allows you to quickly obtain an estimated screen for the presence of alcohol up to 0.400% BAC. Also features a large, easy-to-read orange back-lit LCD display. The AlcoHAWK® PT500P is the ideal unit for law enforcement roadside screening, corrections, probation officers, substance abuse clinics, boating, military, and many other areas of professional testing in which fuel-cell accuracy and reliability is required.

Features

- **PT Core™ electro-chemical fuel-cell sensor**
- **Simple and easy-to-use**
- **Lightweight and compact**
- **Adjustable blowing time**
- **Wireless printing** (printer not included)
- **Temperature monitor**
- **Multiple output conversions**

Specifications

Dimensions	5 in x 2.63 in x 1.25 in	Response Time	3 seconds [1]
Weight	5.2 oz (with batteries)	Blowing Time	5 seconds [2]
Housing	Shock resistant, molded plastic	Operating Temp	23 to 104° F (-5 to 40° C)
Batteries	Two (2) AA Alkaline (included in professional kit)	Detection Range	0.000-0.400% BAC
Battery Life	200 Tests [1]	Sensor Accuracy	±0.005% at 0.05% BAC [3]
Sensor	*PT Core™* Electro-chemical Fuel-cell Sensor	Warranty	One Year Limited Warranty
Warm Up Time	10-20 seconds [1]		

1 Estimates, results may vary.

2 Default setting, professional kit adjustable from 3-8 seconds.

3 Read owner's manual before use to understand proper use, accuracy limitations, and calibration requirements.

4 This device is not to be used to determine if the subject is legal or able to operate any equipment or vehicle.